



Versilon™ WCP Hose

Polypropylene Braided Helically Convoluted Inner Tube Fluoropolymer Hose

Saint-Gobain Performance Plastics' Versilon WCP hose is constructed with a PTFE convoluted inner tube and reinforced with polypropylene braid. The convoluted inner tube is low profile and helically formed to promote drainage. This design enables superior flexibility and vacuum resistance. The polypropylene braid does not conduct internal heat as readily as stainless steel braided hoses and burn potential from accidental contact is greatly reduced.

Versilon WCP hose reduces risk of flavor contamination, does not absorb color and odor, cleans easily with SIP, CIP and can be autoclaved. It is also non-stick and non-contaminating.

Features and Benefits

PTFE inner tube:

- Superior flexibility and vacuum resistance
- Convoluted inner tube is low profile and helically formed to promote drainage
- Low risk of flavor contamination
- Does not absorb color or odor
- Non-stick, non-contaminating
- Easy to clean (SIP, CIP, autoclavable)

Polypropylene braid:

- Ultraviolet (UV) stabilized
- Lightweight
- Does not conduct internal heat as readily as stainless steel braided hoses
- Greatly reduces burn potential from accidental contact

Typical Applications

- Chemical transfer
- Solvent transfer
- Acid lines
- CIP lines
- Food and beverage transfer

Regulatory Compliance

- USDA
- Compliant with FDA 21CFR 177.1550
- US Pharmacopeia Class VI

WCP Hose Specifications

Part Number	Inside Diameter		Outside Diameter		Maximum Working Pressure		Minimum Burst Pressure		Minimum Bend Radius		Vacuum Hg @ 70°F		Weight	
	(in)	(mm)	(in)	(mm)	(psi)	(MPa)	(psi)	(MPa)	(in)	(mm)	(in)	(mm)	(lb/ft)	(kg/m)
2708WCP00	1/2	12.7	7/8	22.2	250	1.72	1,000	6.89	1.75	44.5	29.9	760	0.10	0.15
2712WCP00	3/4	19.1	1-1/4	31.8	250	1.72	1,000	6.89	2.25	57.2	25.0	635	0.19	0.28
2716WCP00	1	25.4	1-1/2	38.1	250	1.72	1,000	6.89	2.75	69.9	22.0	559	0.24	0.36

⚠ Important:

Burst pressure ratings at ambient 70°F (21°C). See applicable notes below on pressure ratings at temperatures other than ambient. Decrease working pressure to 30 psi for all sizes at temperatures above 175°F. Consult factory for higher temperature applications. Data given is for straight hose installation through 250°F.

NOTE: Weights and outside diameter dimensions are nominal. Data given is for hose only. End fitting vs. hose pressure limitations must be considered and the lower of the two ratings must be used on assemblies.

Construction

Inner Tube:	White PTFE	
Reinforcement:	Polypropylene braid -Each strand of large diameter (denier) polypropylene monofilament is twisted and subsequently twined prior to braiding -Tested for maximum abrasion and chemical resistance	
Temperature Rating:	-40°F to +250°F -40°C to +121°C	
Maximum Length:	1/2" 3/4" 1"	100' 100' 100'

Fitting Options

Versilon Crimp Style Fittings

- Over 40 styles of stocked crimp-style fittings in a wide range of materials
- Standard: 316L stainless steel (wetted surfaces)
- Consult factory for other fitting materials

Common Media

- Sulfuric acid
- Hydrofluoric acid
- Caustic solutions
- Hot water cleaning

Hose Cover Options

- Anti-kink casing
- Firesleeve/insulating cover
- Heat shrink/rubber cover
- Silicone slip-on cover

Contact your sales manager or customer service representative for hose cover recommendations to suit your application.

Limited Warranty: For a period of 6 months from the date of first sale, Saint-Gobain Performance Plastics Corporation warrants this product(s) to be free from defects in manufacturing. Our only obligation will be to provide replacement product for any portion proving defective, or at our option, to refund the purchase price thereof. User assumes all other risks, if any, including the risk of injury, loss or damage, whether direct or consequential, arising out of the use, misuse, or inability to use this product(s). SAINT-GOBAIN DISCLAIMS ANY AND ALL OTHER WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE.



Saint-Gobain Performance Plastics
210 Harmony Road
Mickleton, NJ 08056
1-800-435-3992

www.processsystems.saint-gobain.com



NOTE: Saint-Gobain Performance Plastics Corporation does not assume any responsibility or liability for any advice furnished by it, or for the performance or results of any installation or use of the product(s) or of any final product into which the product(s) may be incorporated by the purchaser and/or user. The purchaser and/or user should perform its own tests to determine the suitability and fitness of the product(s) for the particular purpose desired in any given situation.

Versilon™ is a trademark of Saint-Gobain Performance Plastics.